

# P300STD

## Industrial Undecoded Bar Code Scanner



### BAR CODE SCANNERS

#### Optimal Ergonomic Design for Enhanced Industrial Data Capture

Symbol introduces the P300STD undecoded industrial hand-held scanner for reading conventional 1-D bar codes in rugged industrial environments. Utilizing Symbol's high-performance SE1200HP scan engine and superior Phaser ergonomics, the P300STD offers the highest level of scanning efficiency and user comfort available.

#### Designed for Extreme Environments (XE)

The P300STD meets the most stringent industrial standards, earning the Symbol XE class label. It is sealed to the IP54 specification against windblown dust and rain, and withstands multiple 6-ft./1.8 m drops to concrete over the entire temperature range of -22° to 122°F/-30° to 50°C.

Its XE class ruggedness and high-throughput scanning ability make the P300STD an ideal choice for a wide range of 1-D applications in industrial environments such as distribution centers, manufacturing floors and warehouses.

#### Innovative Design Features

As innovative as it is rugged, the P300STD delivers the sophisticated ergonomic and operational features industrial applications demand. The scanner's exit window is scratch-resistant and recessed to prevent damage from direct contact. A twist-to-lock cable seals the scanner and provides superior strain relief. For those applications requiring quick access and out-of-the-way storage, the P300STD comes with a built-in metal hook for attachment to a pulley. And the large, LED-enhancing window makes the "good decode" feedback impossible to miss. The P300STD also utilizes the award-winning Phaser "handle-forward" design making the scanner extremely comfortable to hold and reduces fatigue when scanning throughout a full shift in scan-intensive applications.



Features	Benefits
XE-class durability	Withstands multiple 6-ft./1.8 m drops to concrete
Sealed to IP54 standard	Protected from windblown dust and rain
650 nm laser diode	Easy to see laser beam
Large, bright LED window	Excellent user feedback


#### High-Productivity Scanning

Building on Symbol's experience and leadership in the industrial hand-held scanner market, the P300STD offers numerous hardware and software improvements that deliver better performance and more durability than ever. The P300 uses the SE1200HP scan engine with high-visibility 650 nm laser and Adaptive Logic Technology. Using multiple digitizer thresholds, Adaptive Logic extends the working range on both high-density and poor-quality bar codes. The high-visibility 650 nm laser makes it faster and easier to aim the scanner and read bar codes in sunlight and bright ambient light.

To find out how your company's workforce can be more productive using the P300STD, visit us at [www.symbol.com](http://www.symbol.com)



## P300STD Decode Zone



Note: Typical performance at 68°F (20°C) on high-quality symbols.

## P300STD Specification Highlights

### Physical Characteristics

Dimensions:	6.8 in. H x 5.9 in. L x 2.9 in. D/ 173 mm H x 150 mm L x 74 mm D
Weight:	11 oz./312 gm (without cable)
Power Requirements:	Laser On 100 mA
Power Supply:	Input voltage from 4.75 V to 14 V

### Performance Characteristics

Interface Type:	Integrated RS-232, Wand and Keyboard wedge with additional host interfaces supported by Synapse Smart Cables (USB, OCIA, Dual RS-232, etc.)
Scan Element Type:	Retro-collective
Light Source:	650 nm laser diode/1.2 mW max
Scan Rate:	35 scans per second
Minimum Reflectance Difference:	25% measured at 650 nm
Program Loading:	Parameters set by bar code menus
Decode Capabilities:	UPC-A, UPC-E, EAN 8, EAN 13, Code 39, Tri-Optic Code 39, Code 93, Discrete 2 of 5, Bookland EAN, UPC Coupon Code, Code 39 Full ASCII, Code 128, Interleaved 2 of 5, Codabar, UCC.EAN 128 with full autodiscrimination between all symbologies, MSI Plessey, UPC E1

### User Environment

Operating Temperature:	-22° to 122°F/-30° to 50°C
Storage Temperature:	-40° to 158°F/-40° to 70°C
Humidity:	5% to 95% (non-condensing)
Shock:	Withstands multiple 6-ft./1.8 m drops to concrete
Ambient Light Immunity:	Sunlight: 10,000 ft.-candles, Incandescent, Fluorescent, Sodium Vapor, and Mercury Light: 450 ft.-candles, 4,845 LUX. Immune to direct exposure from normal office and factory level lighting
Environmental Sealing:	IP54 (Industry standard for dust and water sealing)
Agency Approvals:	CDRH Class II, IEC 825 Class II, FCC Class A, UL, CSA, VDE

### Regulatory

Electrical Safety:	Certified to UL1950, CSA C22.2 No. 950, EN60950/IEC950
Laser Safety:	CDRH Class II, IEC Class 2
EMI/RFI:	FCC Part 15 Class B, IECES-003 Class B, European Union EMC Directive

EN410 CE



Specifications are subject to change without notice.

All product and company names are trademarks, service marks or registered trademarks of their respective owners.

For system, product or services availability and specific information within your country, please contact your local Symbol Technologies office or Business Partner.



**Corporate Headquarters**  
**Symbol Technologies, Inc.**  
 One Symbol Plaza, Holtsville, NY 11742-1300  
 TEL: 1-800-722-6234/1-631-738-2400  
 FAX: 1-631-738-5990

**For Asia Pacific Area**  
**Symbol Technologies Asia, Inc.**  
 (Singapore Branch)  
 Asia Pacific Division  
 230 Victoria Street #04-05  
 Bugis Junction Office Tower  
 Singapore 188024  
 TEL: 65-337-6588  
 FAX: 65-337-6488

**For Europe, Middle East and Africa**  
**Symbol Technologies**  
 EMEA Division  
 Symbol Place, Winnersh Triangle  
 Berkshire, England RG41 5TP  
 TEL: 44-118-9457000  
 FAX: 44-118-9457500

**For North America, Latin America and Canada**  
**Symbol Technologies**  
 The Americas  
 One Symbol Plaza  
 Holtsville, NY 11742-1300  
 TEL: 1-800-722-6234/1-631-738-2400  
 FAX: 1-631-738-5990

**Symbol World Wide Web Internet Site**  
 For a complete list of Symbol subsidiaries and Business Partners worldwide contact us at:  
<http://www.symbol.com>  
 E-mail: [webmaster@symbol.com](mailto:webmaster@symbol.com)

