

TATUNG TOUCH SCREEN MONITOR - C5GSE

Screen Size	15" FST (13.7 visible)
Display Area	279 x 210 mm
CRT Dot Pitch	0.28 mm
Treatment	Anti-glare, Anti-static (options)
Scan Rate	30 ~ 57 kHz
Refresh Rate	50 ~ 120 Hz
Maximum Resolution at (refresh rate)	1024 x 768 NI, 70Hz
Recommended Resolution at (refresh rate)	VESA 800 x 600 NI, 85 Hz, flicker-free
Control system	Digital Control, with LED indicators
User controls	Contrast, Brightness, Horizontal Centring, Horizontal width, Vertical Centring, Vertical Height, Pincushion, Trapezoid, Parallelogram, Degauss(or Zoom), Recall
Features	Multi-sync, auto-sizing, full-scan, VESA DPMS power saving, Comply with Emery 2000, DDC 1/2B, Plug&Play, self-test pattern, universal power supply
Low Radiation	MPRII and TCO 99 (option)
Approvals	CE, TUV, EN60950, UL1950, CSA22.22#950, EN50081-1, EN50082-1, VCCI, DHHS, ISO9241-3, SEMKO, NEMKO, DEMKO, FEMKO, FCC Class B, C-Tick, ROV Anlage III
Plug & Play	DDC 1/2B, PC 98 Compliant
Dimensions	335 x 372 x 376 mm (with base)
Net Weight	11.8Kg



2850 El Presidio Street, Long Beach, CA 90810

Tel: 310-637-2105 Fax: 310-637-8484