

TATUNG TOUCH SCREEN MONITOR – PT12G

Screen Panel	12.1 TFT LCD panel
Display Size	246.0 (H) x 148.5 (V) mm
Pixel Pitch	0.264
Display Color	16.7 million
Contrast Ratio	150:1
Luminance	180 cd/m ²
Viewing Angle	100°(horizontal), 40°(vertical)
Input Signal and Connector	Analog RGB 15-pin mini D-sub VGA Connector
Power Input	100V – 240V AC @50/60 Hz External AC Adapter
Resolution	1024 x 768 (max)
Scanning Frequency	24 – 69 kHz (horizontal) 50 – 85 Hz (vertical)
User Control	Power on/off, OSD, Contrast, Brightness, Video Level, Auto-adjust, Color Temperature, OSD H-Position, OSD V-Position, Display Mode Detection, Gamma, Frame, Clock, Phase Default Size, Native Size, H-size, V-size, Graph/Text mode
Features	Flicker and Static free less than VLMF Radiation standard, panel & base detachable. Can be flushed mounted on a wall.
Approvals	UL, C-UL, TUV/GS, CE FCC-B, VCCI, EPA
Touch Screen Options	Capacitive, Surface Acoustic Wave, or Resistive Membrane



2850 El Presidio Street, Long Beach, CA 90810

Tel: 310-637-2105 Fax: 310-637-8484