

UROVO

Thermal Transfer Label Printer D8130 Plus

- Featuring a shell-type flip-top cover for effortless label loading.
- 400 MHz 32-bit ARM9 high-performance processor paired with 128MB SDRAM and 128MB Flash for enhanced efficiency.
- High-speed printing with speeds of up to 152mm (6 inches) per second.
- Multi-command compatibility, emulating TSPL, EPL, ZPL, ZPL II, and DPL.
- Supports USB Host 2.0 for connecting barcode scanners or PC keyboards, enabling easy data input and on-demand printing.
- Ideal for retail, medical, inventory management, asset management, and other applications, supporting text, barcode, and graphic printing.



Thermal transfer
& direct thermal
printing



Easy to replace
paper roll and
printer ribbon



Rich communication
and printing
interfaces



High-speed and
high-efficiency
printing



High-
specification
configuration



D8130 Plus Thermal Transfer Label Printer

UROVO

Specifications

Printing Specifications

Print methods: Direct Thermal/Thermal Transfer
Firmware emulates: TSPL, EPL, ZPL, ZPL II, DPL
Resolution: 300DPI
Maximum print speed: Max. 152mm/s
Maximum print width: 108.4mm
Maximum print length: 11,430mm
Label paper length: 5~11,430mm

Barcode Printing

1D Barcode: Code 93, Code 128 (subsets A, B, C), UPC-A, UPC-E, UCC-128, Codabar, EAN/JAN-8, EAN/JAN-13, Interleaved 2 of 5, ITF14, MSI Pleassy, PostCode, Telepen

2D Barcode: QR Code, Micro QR Code, PDF417, Micro PDF417, MaxiCode, Aztec Code, Data Matrix

User Interface

Power switch: 1
Buttons: 1 (Feed)
LED lights: 5 (Online-Blue, Error-Red, Ribbon-Green, Communication-Orange, Press key-White)
Touch panel: /

Communication Interface

- USB 2.0 High Speed 480Mbps
- USB Host 2.0, for scanner or PC keyboard
- Ethernet 10/100Mbps
- RS-232
- Internal Bluetooth 4.0 (factory option)
- Internal Wi-Fi (factory option)

Sensor

- Head open sensor
- Ribbon out sensor
- Reflective sensor (moveable)
- Transmissive sensor (moveable)
- Cutter Module with Pickup Sensor

Physical Parameters

Dimensions: 280mm * 190mm * 198.3mm
Weight: 2.7kg (D8120 Plus/D8130 Plus)

Optional

- Distributor options:
- Guillotine cutter
 - Peeler

Media Type

Media type: Continuous, die-cut, black mark, fan-fold(outside wound), Linerless Label
Media width: 20~118mm
Media thickness: 0.06~0.254mm
Diameter: Maximum 127mm

Fonts

8 alpha-numeric bitmap fonts
True type font engine (need to download scalable font file)

Ribbon

Outer Diameter: Maximum 67mm
Ribbon Length: 300m
Width: 30~110mm
Winding Type: Outer roll type

Environment

Operating environment: 5~40°C, 20~90% (no condensation)
Storage environment: -25~55°C, 20~93% (no condensation)

Memory

128MB SDRAM
128MB Flash Memory

Battery

Input: AC 100-240V, 2.5A
Output: DC 24V, 2.5A
External universal switching power supply

CPU

400 MHZ
32 bits, ARM9

Accessories

- Quick installation guide
- USB cable
- Power cable
- 1-inch ribbon*2
- External universal switching power supply

UROVO PTE. LIMITED

Website: en.urovo.com

Email: urovo@urovo.com

Address: 1 Raffles Place, #21-01 One Raffles Place Tower 1, Singapore 048616

Urovo Europe

Website: europe.urovo.com

Email: sales-europe@urovo-emea.com

Address: de Maas 9, 5684PL, Best, the Netherlands

Urovo North America

Website: us.urovo.com

Email: urovo@urovo.com

Address: 1990 Main Street, Suite 750, Sarasota, Florida 34236

***This page is subject to change without prior notice**