VP500 / VP550





Right Labels, Right Time, Right Cost.







MAKE LABELING SIMPLE

VP500/VP550 produces professional-quality labels for all your small-batch specialty products. Whether you are new to digital labeling or upgrading your thermal printer, these budget-friendly printers help you print brilliant color labels fast and timely in the correct quantity. And cost-effectively every time.

Key benefits:

- ✓ High Speed Print 1,000 (6 x 4") labels in less than 10 min.
- ✓ Brilliant color quality Image
- Large individual ink tanks
- ✓ Enhanced water-resistant inks (with VP550)
- ✓ Food safe & Environmentally friendly dye ink formula



Asia Office

Email: asia@vipcolor.com Phone: +65 6482 1755 Web: vipcolor.com

China Office

Email: asia@vipcolor.com Phone: +86 21 3898 4898 x 8210 Web: vipcolor.com/zh

Europe Office

Email: info@vipcoloreurope.com Phone: +34 93 588 3018 Web: vipcoloreurope.com

US Office

Email: sales@vipcolor.com Phone: 1 800 404 3185 Web: vipcolor.com

DESKTOP COLOR LABEL PRINTERS VP500 / VP550



TECHNICAL SPECIFICATIONS

	VP500	VP550
Print speed	6 and 8 ips (154 and 203 mm/second)	
Print resolution	1,600 x 1,600 dpi and 1,600 x 800 dpi	
Print width/Length	2" - 8.5" (51 - 216 mm) / Up to 40" (1.016 m)	
Comm ports	USB 2.0, 10/100Base-T, GPIO	
Inks	Five individual 200ml dye	Five Indvidual 200ml (Enhanced water resistant) dye
Time to first label	Less than 10 seconds	
Print modes	Roll-to-Cut, Roll-to-Roll, Print & Hold	
Barcode PQ	Grade B or better for • 1D barcode (Code 39) with 10 mils bar width • 2D barcode (PDF417) with 10 miles cell size	
Electrical	Universal power supply - 100-240 Vac, Peak current < 4A	
Temperature	Operation: 15 to 35°C at RH 20 -80%; Storage: -5 to 50°C	
Safety/ Compliant	FCC Part 15, Subpart B, Class A (US), cULus, IEC-62368-1, RCM, CCC, UKCA mark, Singapore Safety Mark	
User Interface	Embedded web server, Backlit LCD control panel in 9 languages, LED for warning and readiness indication	
Acoustics	Sound pressure level < 60 dBA	
Printer Driver	Windows™ 10 and above	
Supported Software	All major Windows based label and graphic design applications like Adobe illustrator, Nicelabel, Bartender.	
Sensor type	Gap, Reflective sensor for black mark	
Media type	Roll (continuous, die-cut), fan-fold	
Media thickness	0.1 - 0.3 mm	
Roll diameter	8" (203 mm) OD with 3" (76 mm) core	
Supported media	Glossy, matte, synthetics	
Others	Rugged metal casing, automatic cutter, patented print & hold mechanism	
Warranty	1 year warranty or 5M inches, whichever earlier	

Label Printer comes with unwinder



- High Speed Print
- Brilliant color quality Image
 Fine text, barcode and variable data



PRINTING YOUR OWN LABELS IS

AS SIMPLE AS ABC



Design the label





Load the blank **labelstock**



Print the label



Paste on your product

ACCESSORIES



Re-winder



Label Slitter



Matrix Remover & Slitter





