

Twenty-six years of Expertise Bring Versatile Indoor Domes.



Indoor Domes

Our general purpose Indoor Domes are effectively used for virtually any indoor application. Videolarm Indoor Domes deliver the high-tech surveillance you need with the added flexibility of choosing your own camera lens.

IFD8-Indoor FusionDome™



- Pendant mount, available as wall mount
- Accepts many manufacturer's unitized camera systems or single fixed camera
- IP66, designed to meet NEMA1 for falling dirt ingress
- Clear or tinted dome (1 F stop light reduction)
- **Dimensions:**
Dome - 8"
Housing Height (to top of pendant) - 12.5"
Housing Diameter - 11.5"
- **Brackets available for JVC, Canon, Axis, and Panasonic network cameras**
- **Available as S-View model**

MP123/163 MiniPan



- Pendant mount, available as wall mount
- Clear or tinted dome (1 F stop light reduction)
- Liner available
- MP123 available with scanner
- MP163 can take multiple fixed cameras
- White ABS plastic upper body
- **Dimensions:**
Dome - MP123: 12"
MP163: 16"
Housing Height (to top of pendant) - 15.2"
Housing Diameter - MP123: 14.25"
MP163: 18.1"

MP121/141 MiniPan



- Recessed ceiling mount
- Clear or tinted dome (1 F stop light reduction)
- Standard white or optional brass finish trim rings
- Easy to install and service
- MP141 accepts multiple fixed cameras
- Liner available
- **Dimensions:**
Dome - MP121: 12"
MP141: 14"
Housing Height: MP121: 13.5"
MP141: 14.3"
Housing Diameter - MP121: 16.875"
MP141: 17"

OH121/161/201 ObservaDome™



- Recessed 2x2 ceiling mount
- Complete with adjustable swivel head
- Includes dust cover and liner (not available in Econo Series)
- OH161/166 and OH201/206 accept multiple fixed cameras
- Clear or tinted dome (1 F stop light reduction)
- Dummy domes available
- **Dimensions:**
Dome - OH121: 12"
OH161 - 16"
OH201 - 20"
Housing Height - OH121: 12.6"
OH161: 14.6"
OH201: 16.6"
Housing Width - 24"

O124 ObservaDome™




- Recessed 2x2 ceiling mount
- Liner included
- Lightweight fire retardant plastic body
- Clear or tinted dome (1 F stop light reduction)
- Can be serviced from below ceiling
- **Dimensions:**
Dome - 12"
Housing Height - 10.75"
Housing Width - 24"

OP123/163 ObservaDome™




- Pendant ceiling mount
- Rugged black ABS upper body
- Clear or tinted dome (1 F stop light reduction)
- Complete with adjustable swivel head mount
- OP163 can take multiple fixed cameras
- **Dimensions:**
Dome - OP123: 12"
OP163: 16"
Housing Height - OP123: 14"
OP163: 18"
Housing Diameter - OP123: 14.25"
OP163: 18.36"

M7/12 MicroDome™




- Recessed ceiling mount
- Clear or tinted dome (1 F stop light reduction)
- Flame resistant plastic upper body
- M7 includes liner, M12 includes silk-screened dome with pre-cut viewing window
- Easy installation and servicing
- **Dimensions:**
Dome - M7: 7"
M12: 12"
Housing Height - M7: 14.75"
M12: 20.25"
Housing Diameter - M7: 9.75"
M12: 14.375"

MR5/7 MicroDome™



- Recessed ceiling mount
- Complete with fixed camera mount bracket
- Plenum rated metal top
- Clear or tinted dome (1 F stop light reduction)
- Liner included
- Includes decorative trim ring
- **Dimensions:**
Dome - MR5: 5"
MR7: 7"
Housing Height - MR5: 8.6"
MR7: 9"
Backbox Width - MR5: 6.5"
MR7: 9.75"
Trim Ring Diameter - MR5: 8.4"
MR7: 12.25"
- **MR5 available as VideoKit™ model**
- **MR7 available as S-View™ model**

OH081TL ObservaDome™



- Full 360° viewing capability
- Replaces 2 x 2 ceiling tile
- Low profile 8" dome
- Tinted dome (1 F stop light reduction)
- Dust cover
- **Dimensions:**
Dome - 8"
Housing Height - 9.5"
Housing Width - 24"
- **Available as VideoKit™ model**

QD8T Quarter Dome



- Corner Mount
- Tinted cell cast acrylic dome (1 F stop light reduction)
- 18-gauge steel mounting frame
- Fully adjustable steel camera bracket
- Complete with gold and silver accent trim
- **Dimensions:**
Housing Width - 15.5"
Housing Height - 9.125"
Housing Depth - 10.75"
- **Available as Q-View™ model**

HD7T Half Dome



- Wall Mount
- Tinted cell cast acrylic dome (1 F stop light reduction)
- 18-gauge steel mounting frame
- Fully adjustable steel camera bracket
- Complete with gold and silver accent trim
- **Dimensions:**
Housing Width - 18"
Housing Height - 8.125"
Housing Depth - 10.5"
- **Available as Q-View™ model**

MAXIMUM FIXED CAMERA/LENS LENGTHS				
Model	One Camera	Two Cameras	Three Cameras	Four Cameras
HD7T	8"			
IFD8	7.5"			
M7	8"			
M12	11"			
MP121	8" liner 9" w/o			
MP123	8" liner 9" w/o	7"		
MP141	10" liner 11" w/o	7" liner 8" w/o		
MP163	12" liner 13" w/o	7"		
MR5	5"			
MR7	8"			
OH081	8"			
OH121	8"			
OH161	12"	10"		
OH201	15"	14"	9.5"	5"
O124	9"	7"		
OP123	8"	7"		
OP163	12"	8"	6"	
QD8T	8"			