

# 46" Narrow Bezel Commercial LED Display

Simple Multimedia Scheduling and Playback

### **CDE4600-L**



The ViewSonic<sup>®</sup> CDE4600-L is a 46" commercial LED display with a 19.5mm narrow-bezel design. Featuring Full HD 1080p resolution, 350-nit high brightness, 4000:1 high contrast ratio, SuperClear® technology for wide viewing angles, and dual 7W stereo speakers, the CDE4600-L delivers sharp, vivid images with incredible sound for superior multimedia messaging performance. Versatile connectivity options include HDMI, DVI, D-Sub, YPbPr, and CVBS inputs for easy installation and control of a variety of high-definition devices. Integrated RS232 input and output, with IR pass-through and a one-time setting function, make the CDE4600-L an easy-tomanage solution for multiple display configurations. An integrated media player supports the scheduling and playback of photo, music, and video content directly from a USB drive. Content can also be loaded and distributed to multiple displays via LAN RJ45 connection, or wirelessly from mobile devices. The ViewSonic CDE4600-L is the ideal digital signage solution for attracting customers in shopping malls, retail outlets, restaurants, and other indoor commercial areas.

#### Sleek, Narrow Bezel Design

ViewSonic's CDE4600-L features a 19.5mm narrow bezel design. This sleek, narrow bezel maximizes impactful visual messaging for passersby, making the CDE4600-L the perfect choice for digital signage installations.

### Full HD 1080p for Superior Pixel Performance

Full HD 1920x1080 resolution delivers superior pixel-by-pixel performance for a more realistic viewing experience. At this resolution, greater image clarity and detail brings high-definition multimedia content to life.

# Easy LAN and Wireless Content Uploading from PCs and Mobile Devices

The CDE4600-L features a RJ45 port to connect directly with PCs or notebooks via Intranet connection. This provides for the efficient loading of content onto multiple displays through a primary display. DLNA-compatible mobile devices can also utilize a wireless hub to push multimedia content directly to selected displays.

# USB Multimedia Player for Scheduled Playback of Videos, Photos and Music

With the handy PC-less USB playback feature, photos, music and 1080p video can be immediately displayed on-screen from a USB drive. A userfriendly on-screen scheduling interface also lets you select time and date, as well as repeat and shuffle settings, or choose specific content to play from the attached USB source.

### RS232 In/Out with IR Pass-Through for Easy Management

RS232 input and output connectivity, along with IR pass-through functionality, provides for the easy and efficient management of multipledisplay configurations from a single notebook or PC.

# 46" Narrow Bezel Commercial LED Display



## CDE4600-L



Versatile Inputs and One-Time Configuration Settings

With a versatile selection of inputs, including HDMI, DVI, CVBS, YPbPr (YCbCr) and VGA, the CDE4600-L commercial display enables you to easily connect and use a variety of digital equipment. Best of all, the one-time display installation and setup feature means your preferred source settings are never lost.

46'

8ms

16:9

VGA

1920 x 1080

4000:1 (typ)

350 cd/m<sup>2</sup> (typ)

RS232, RJ45

3-pin plug

88W (typ)

Hard coating (3H)

Internal 7-watt (x2)

Format and edges

480i, 480p, 720p, 1080i, 1080p

178º horizontal, 178º vertical

Long life, 30,000 hrs. (typ)

TFT LED Module with LED Backlight

40.1" horizontal x 22.5" vertical; 46" diagonal

HDMI, DVI, component, CVBS, VGA, CVBS (BNC)

15-pin mini D-sub (VGA), RCA Audio In, headphone out

POWER, MUTE, INPUT, VOL -/+, UP, DOWN, MENU

Colour, Sharpness, Advanced, Game or Computer,

USB scheduling, Sleep timer, Auto switch off, Control settings, Factory settings View network settings, Network configuration

AC 100-240V (universal), 50-60Hz

Picture style, Restore style, Backlight, Contrast, Brightness,

Sound style, Restore style, Bass, Treble, Audio out, Advanced

Menu language, Monitor ID, Eco mode, Auto search, Clock,

Static IP configuration, Digital Media Render, Network name

HDMI, DVI-D, DisplayPort, YPbPr, CVBS, USB

### **Applications**

- Indoor commercial environments
- · Retail digital signage small to mid-size business
- · Sports bar and restaurant entertainment displays

Type Display Area

#### **Optional Accessories**

Specifications PANEL

INPUT

AUDIO OUTPUT

INPUT SIGNAL

CONNECTOR

CONTROLS

POWER

Stand .....STND-021 Wall Mount Kit .....WMK-014

> Optimum Resolution Contrast Ratio

Viewing Angles

Response Time

Light Source Brightness

Aspect Ratio

Video Input

Speakers

Analog

Digital

Power

Panel

Picture

Sound

Voltage Consumption

Video Output

Control Input/Output

TV/Video Comp.

General Settings

Network Settings

Panel Surface

## 42.0' 1.5' VESA® Wall Moun 400mm x 400mn 24.5 enu Control: .... Internal Speake Internal Speaker . معمد معدن 660881 200 Slim Design HDMI DVI LAN VGA YPbPr In/Out In/Out USB 19.5 mm SPDIF RS232 19.5 mm

Bezel \	Nidth
---------	-------

OPERATING CONDITIONS	Temperature Humidity	32–104°F (0–40°C) 20–80% (non-condensing)
DIMENSIONS (W x H x D)	Physical Packaging	42.0 x 24.5 x 1.5 in. / 1068 x 622.5 x 38.8 mm 45.8 x 30.2 x 5.8 in. / 1164 x 768 x 148 mm
BEZEL DIMENSIONS	Left/Right Top/Bottom	19.5mm / 19.5mm 19.5mm / 19.5mm
WEIGHT	Net Gross	33.7 lb. / 15.3 kg 37.8 lb. / 17.2 kg
WALL MOUNT	VESA <sup>®</sup>	400mm x 400mm
REGULATIONS		CE, CB, WEEE, C-tick, FCC, ICES003, UL/cUL, CE, CB, CU, ENERGY STAR 6.0
RECYCLE/DISPOSAL		Please dispose of in accordance with local, state or federal laws.
WARRANTY		Three-year limited warranty on parts, labor and backlight

#### What's in the box?

CDE4600-L display, power cable, VGA cable, remote control with batteries, Quick Start Guide, ViewSonic Wizard CD (with User Guide)



have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

Specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. HDMI, the HDMI Logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2014 ViewSonic Corporation. All rights reserved. [17312-00B-07/14]