10.1" All-in-One Electronic Mini Billboard



Motion-Activated Custom Multimedia Messaging

EP1031r



The ViewSonic® EP1031r is a 10.1" multimedia all-inone electronic mini billboard. It delivers eye-catching commercial messaging at retail POS, hotel lobbies and front desks, conference and exhibition venues, and other high-visibility locations. The EP1031r features wireless b/g/n network and LAN connectivity for easy loading of content, and supports Power over Ethernet (PoE) for convenient one-wire installation. Boasting an exclusive integrated motion sensor, 6 touch-screen control keys, and bundled Signage Manager Express software, the EP1031r effectively delivers customized messaging to target audiences. Its built-in media player, 4GB internal storage, and integrated speakers enable the playback of video clips, as well as photos and music, from a USB hard drive or SD/SDHC memory card. With VESAmount compliance (75mm x 75mm), and W3C and SMIL compatibility, the EP1031r provides versatile options to display creative brand messaging.

Perfect Size for Up-close, High-impact Messaging

The ViewSonic EP1031r all-in-one electronic mini billboard has a 10.1" LED display area with 800 x 480 resolution. With its compact design, the EP1031r can be deployed anywhere, including retail shelf edges, hotel front desks, in meeting rooms, or on classroom doors. The EP1031r features 300-nit brightness and a 500:1 contrast ratio to deliver high-impact, quality messaging that will attract the attention of passersby.

Advanced Motion Sensor and 6 Programmable Touch Keys

Equipped with an advanced motion sensor, the EP1031r can display customized content whenever movements of nearby people are detected. And with 6 highly visible and easy-to-use programmable touch keys, users can directly interact with brand offerings and retail messaging.

Convenient One-wire Installation via Power over Ethernet

The EP1031r utilizes state-of-the-art Power over Ethernet (PoE) technology for one-wire installation. This allows you to easily power and connect your displays with just a single cable. PoE also allows you to create multi-display digital signage installations, while reducing installation costs.

4GB of Internal Memory and SD/SDHC Card Slot

The EP1031r is capable of storing and playing hours and hours of high-definition multimedia content thanks to its 4GB of built-in, shock-resistant, solid-state memory. This reliable all-in-one electronic mini billboard will display dynamic content with no crashes, freezes, or lost content.

10.1" All-in-One Electronic Mini Billboards



EP1031r



LAN

Easy Loading of Content through Wireless/ RJ45 Ethernet


The EP1031r integrates wireless 802.11 b/g/n network and RJ45 Ethernet connectivity, providing a convenient and efficient way to load content from a PC or laptop connection. Wireless/LAN connectivity can also be used to remotely load content to multiple displays.



Support for Dynamic W3C/SMIL-format Presentations

With the bundled Signage Manager Express software, the EP1031r can display W3C, HTML5, and SMIL content retrieved from the Internet. Display fresh and interesting content such as news, weather information, stock market trends, sports scores, social networking, or RSS feeds on multiple screens.





Specifications		
PANEL	Type Display Area Optimum Resolution Contrast Ratio Viewing Angles Response Time Light Source Brightness Panel Surface	10.1" TFT LCD Module with LED Backlight 8.6" horizontal x 5.2" vertical; 10.1" diagonal 800 x 480 500:1 (typ) 170° horizontal, 160° vertical 30ms Long life, 50,000 hrs. (typ) 300 cd/m² (typ) Anti-glare
CONNECTIVITY	Digital USB LAN Audio Out Card Reader	HDMI 1.3 Type A x2 (content loading, F/W upgrade, keyboard/mouse) Type B x1 (for F/W troubleshooting) RJ45 3.5mm mini jack SD/SDHC
FILE FORMATS	Video Audio Photo Dynamic	MPEG 1,2,4, WMV MPEG L2, MP3 JPG, PNG W3C HTML5, W3C SMIL 3.0
AUDIO	Speakers	2W (x2)
WALL MOUNT	VESA	75 x 75mm
POWER	Voltage Consumption	AC 100–240V (universal), 50–60Hz 12.6W (typ)
OPERATING CONDITIONS	Temperature Humidity Altitude	32°F-104°F (0°C-40°C) 5%-85% (non-condensing) 0-6,561 ft (2,000m)
DIMENSIONS (W x H x D)	Physical Packaging	10.9 x 7.3 x 1.6 in. / 278 x 186 x 40 mm 12.6 x 10.0 x 3.5 in. / 320 x 255 x 89 mm
WEIGHT	Net Gross	4.7 lbs. / 2.1 kg 7.3 lbs. / 3.3 kg
REGULATIONS		FCC, CE
WARRANTY		1-year limited warranty on parts and labor

What's in the box?

EP1031r ePoster, AC adapter, ethernet cable, 3.5mm to RCA AC adapter, display stand and screws, Quick Start Guide, Software Setup Guide, ViewSonic Wizard CD (User Guide and Signage Manger Express software)



Programs, specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2013 ViewSonic Corporation. All rights reserved. [16927-00B-11/13]