VA1913w

19" (18.5" VIEWABLE) 16:9 WIDESCREEN LCD

WITH 10,000:1 DYNAMIC CONTRAST RATIO

Widescreen for work and play.

ViewSonic's 19" VA1913w 16:9 widescreen features automatic aspect ratio adjustment that ensures a full, undistorted screen image. High brightness and fast video response deliver brilliant, blur-free images, while the ultra-high 10,000:1 dynamic contrast ratio produces greater detail and definition especially in darker images. This widescreen LCD continues ViewSonic's tradition of brilliant image quality and reliable performance all at an appealing price point. The VA1913w is the right choice for home/small office users, students, gamers and corporate professionals.



WORK FASTER. PLAY MORE.

- > Widescreen aspect ratio with 1366x768 resolution
 The widescreen aspect ratio allows you to view HD content in its native format with no stretching or distortion.
- > 10,000:1 dynamic contrast ratio
 Provides darker black levels and better overall
 front-of-screen performance.
- > ClearMotiv® 5ms video response time Fast 5ms video response enables digital HD broadcast-quality video.
- Eco-mode Environmentally-friendly Eco-mode reduces power consumption and extends backlight life.
- > Aspect ratio adjustment
 Eliminates image distortion by maintaining correct image proportions for both widescreen and native 4:3 content.















VA1913w

19" (18.5" VIEWABLE) 16:9 WIDESCREEN LCD WITH 10,000:1 DYNAMIC CONTRAST RATIO







LCD	Size	18.5" wide Color TFT Active Matrix LCD 16:9 aspect ratio
	Display Area	16.3" horizontal x 9.0" vertical; 18.5" diagonal
	Optimum Resolution	1366×768
	Brightness	250 cd/m² (typ)
	Contrast Ratio	1000:1 static (typ); 10,000:1 dynamic
	Viewing Angles	170° horizontal, 160° vertical (CR≧10)
	Response Time	5ms (typ)
	Pixel Pitch	0.3mm horizontal x 0.3mm vertical
	Panel Surface	Anti-Glare, hard coating (3H)
	Light Source	Long life, 50,000 hrs. (typ)
	Color Support	16.7 M (6-bits + Hi FRC) panel
INPUT	Analog	RGB Analog (75 ohms, 0.7 / 1.0 Vp-p)
	Sync	Separate Sync
	Frequency	F _h : 24–82kHz, F _v : 50–85Hz
COMPATIBILITY	PC	VGA up to 1366x768 non-interlaced
	Mac [®] *	Power Mac [™] up to 1366x768
CONNECTOR	Analog	15-pin mini D-sub (VGA)
	Power	Built-in power Adapter, 3-Pin plug
POWER	Voltage	AC 100–240V (Universal); 50/60Hz (Switch)
	Consumption	20W
	Sleep mode	≦1W
ERGONOMICS	Tilt	Up 20°, down -5°
CONTROLS	Basic	[1], [2], Power, Down[▼], Up[▲]
	OnView	Auto Image Adjust, Contrast/Brightness, Color Adjust (sRGB, 9300K,
		7500K, 6500K, 5000K, User Color [R, G, B]), Information, Manual Image
		Adjust (H/V Position, Horizontal Size, Fine Tune, Sharpness), Dynamic
		Contrast, Aspect Ratio, Eco-mode, Setup Menu (Language Select,
		Reslotuion Notice, OSD Position, OSD Time Out, OSD Background),
		Memory Recall
OPERATING	Temperature	41–95° F (5–35° C)
CONDITIONS	Humidity	20–80% (non-condensing)
DIMENSIONS	Physical with stand	17.6" x 13.8" x 7.8 (447mm x 350mm x 199mm)
(WxHxD)	Physical without stand	17.6" x 10.6" x 2.46 (447mm x 268mm x 63mm)
	Packaging	20.0" x 16.0" x 5.0 (508mm x 415mm x 126mm)
WEIGHT	Net with stand	7.5 lb. (3.4 kg)
	Net without stand	6.7 lb. (3.0 kg)
	Gross	10.2 lb. (4.6 kg)
REGULATIONS		CB, TCO'03, WEEE, RoHS, UL/cUL, FCC-B, IRAM, NOM, NEMKO/ERGO, CE,
		Ukraine, GOST-R+Hygienic, SASO, BSMI, PSB, C-TICK, MIC, VCCI, CCC
RECYCLE/DISPOSAL		The lamp in this product contains mercury. Please dispose of in
		accordance with local, state or federal laws.
WALL MOUNT		VESA 100mm x 100mm
PACKAGE CONTENTS		LCD display, power cable, video cable, Quick Start Guide
WARRANTY		Three-year limited warranty on parts, labor and backlight.











Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2010 ViewSonic Corporation. All rights reserved. [15019-02B-07/10] VA1913w-14

