

VT2730

27" FULL 1080P LCD HDTV
WITH 100,000:1 DYNAMIC CONTRAST RATIO

Feature packed – entertainment plus.

Feel the action in movies, games and sports on the 27" VT2730 widescreen LCD HDTV. Full HD 1080p resolution delivers 100% of your HD signal for incredibly precise images. High brightness combines with 100,000:1 dynamic contrast ratio for unparalleled definition and detail. Super-fast 3.4ms video response and advanced image processing ensures extreme clarity in all your HD entertainment. The integrated ATSC/NTSC/QAM tuner and multiple connectivity options including HDMI give you all the inputs you need for game consoles, DVD and Blu-Ray™ players and computers. Get maximum enjoyment in your smaller spaces or on your desktop with the stylish, versatile VT2730 LCD HDTV.



IDEAL FOR SMALL LIVING SPACES

- > **16:9 Full HD 1920x1080 resolution panel**
Experience a new dimension in movie viewing and gaming with Full HD 1080p super resolution for the optimum richness and clarity in picture quality
- > **Advanced image processing delivers clearer, crisper, sharper images**
Advanced ClearPicture™ image processing eliminates noise, increases contrast and detail and optimizes color for rich, vibrant images. High-definition images look amazing and even standard television images are unbelievably smooth and sharp.
- > **Vivid graphics, clear text, stunning TV**
Ultra-high brightness of 250-nit (typ), dynamic contrast ratio of 100,000:1 and 1920x1080 optimum PC resolution provide vibrant video and crisp data images in the living room or on the desktop.
- > **OptiSync® technology now features HDMI**
Add versatility to your LCD TV with support for HDMI with high-definition content protection (HDCP) and analog (VGA) signals, plus component, S-video, composite, and TV/cable input.
- > **USB port JPEG picture format**
Use as a digital photo frame with slideshow control function



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference® 

VT2730

27" FULL 1080P LCD HDTV WITH 100,000:1 DYNAMIC CONTRAST RATIO



ISO 9001:2000
FM 40187



ISO 14001:1996
FM 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

LCD	Type	27" Wide Color TFT Active Matrix LCD
	Display Area	23.5" horizontal x 13.2" vertical; 27.0" diagonal
	Optimum Resolution	1920x1080
	Contrast Ratio	1200:1 static (typ), 100,000:1 dynamic
	Viewing Angles	170° horizontal, 160° vertical
	Response Time	3.4ms
	Light Source	Long life, 40,000 hrs. (typ)
	Brightness	300 cd/m ² (typ)
	Aspect Ratio	16:9
	Glass Surface	Anti-glare, anti-reflective coat
INPUT	PC	RGB analog (75 ohms, 0.7 Vp-p)
	TV/Video	TV/cable, composite (RCA), component YPbPr/YCbCr, S-Video
	Audio	3.5mm mini stereo audio in, earphone out and RCA (left/right) audio in
	Frequency	F _H : 30~64kHz, F _V : 60~75Hz
	Sync	H/V separated (TTL)
	Digital	HDMI (x3) with HDCP and audio support
	Tuner	ATSC/NTSC/QAM
	USB	JPEG
AUDIO OUTPUT	Speakers	2x5-watt
COMPATIBILITY	PC	1920x1080 @ 60Hz (preferred), 1920x1080 @ 60Hz
	Mac®*	G3/G4/G5 up to 1920x1080
INPUT SIGNAL	TV/Video Comp.	480i, 480p, 720p, 1080i, 1080p
CONNECTOR	Analog	15-pin mini D-sub (VGA)
	Digital	HDMI (x3)
	Power	3-pin AC plug
POWER	Voltage	AC 100~240V (universal), +/-10% Wide Range
	Consumption	70W (typ) / 75W (max.)
CONTROLS	Basic	Vol +/-, menu, channel down/up, source, power
	Picture	Picture mode, contrast, brightness, sharpness, tint, color, color mode, zoom mode
	Picture (Video mode)	Picture mode, contrast, brightness, sharpness, color mode
	Picture (PC mode)	Picture mode, contrast, brightness, sharpness, color mode, advanced
	Channel	TV source, auto scan, favorite, show/hide, channel number, channel label, DTV signal
	Lock	Change password, system lock, unrated lock, input block, US, Canada, RRT setting, reset RRT
	Option	Menu language, transparency, OSD time out, closed caption, dynamic contrast ratio (DCR), restore default
	Time	Sleep timer, time zone, DST, time format, auto sync, clock
	Audio	Sound mode, treble/bass, prefer language, surround sound, audio only
	ERGONOMICS	
OPERATING CONDITIONS	Temperature	32~104°F (0~40°C)
	Humidity	10~65% (non-condensing)
DIMENSIONS (W x H x D)	Physical with stand	25.4" x 18.3" x 0.9" (646mm x 466mm x 228mm)
	Physical without stand	25.4" x 16.1" x 2.9" (646mm x 410mm x 75mm)
WEIGHT	Net with stand	15.4 lb. (7.0 kg)
	Net without stand	12.2 lb. (5.6 kg)
	Gross with stand	19.5 lb. (8.6 kg)
WALL MOUNT		200mm x 100mm
REGULATIONS		FCC, cUL (UL), RoHS, NOM, BETS-7, CB
RECYCLE/DISPOSAL		The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws.
PACKAGE CONTENTS		LCD TV display, power cable(s), remote control with batteries, Quick Start Guide, User Guide
WARRANTY		One-year limited warranty on parts and backlight

Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2010 ViewSonic Corporation. All rights reserved. [14883-01B-07/10] VT2730-1

ViewSonic®
See the difference® 

For more product information, visit us on the web at ViewSonic.com