

VX1932wm-LED

19" WIDESCREEN LCD

WITH 10,000,000:1
DYNAMIC CONTRAST RATIO

Eco-friendly and picture perfect.

ViewSonic's new VX1932wm-LED WLED backlight is the newest addition to a green-line of LCD monitors. With dynamic contrast ratio at 10,000,000:1 you get a true-to-life picture depth and clarity in any room. Backlight WLED automatically detects image signal and intelligently controls backlight brightness — making the black, pure black in a dark scene and the white, "whiter" in a bright environment. It also automatically adjusts gray level and enhances the LCD monitor's gray level performance range. Perfect for office applications, multimedia applications, internet browsing and anyone who wants to reduce their energy bills. It uses 50% less power without compromising your viewing quality and has eco-friendly mercury free WLED backlight.



AMAZING GAMES AND HD CONTENT

- > Full 19" viewable widescreen mercury-free WLED backlight
- > 50% energy savings
- > 10,000,000:1 dynamic contrast ratio
- > Stylish slim-bezel design
The thin bezel lets you see more without taking up valuable desktop real estate. The floating head design accentuates the visual experience.
- > OptiSync® digital/analog inputs expand your connectivity
Multi-mode input technology supports both digital (DVI) and analog (VGA) signals for ultimate compatibility and configuration flexibility.
- > Multimedia enhanced
Save desk and workspace and enjoy rich, stereo sound with built-in stereo speakers.
- > Windows Vista approved
- > PC and Mac® compatible
- > MPR II and ENERGY STAR® 5.0 qualified



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference® 

VX1932wm-LED

19" WIDESCREEN LCD WITH 10,000,000:1 DYNAMIC CONTRAST RATIO



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.



LCD	Type	19" Wide Color TFT Active Matrix LCD
	Display Area	16.1" horizontal x 10.0" vertical; 19" diagonal
	Optimum Resolution	1440x900
	Contrast Ratio	1000:1 (typ); 10,000,000:1 (dynamic)
	Viewing Angles	170° horizontal, 160° vertical @ contrast ratio > 10:1
	Response Time	5ms (typ)
	Light Source	Long life, 30,000 hrs. (typ)
	Brightness	250 cd/m ² (typ)
VIDEO INPUT	Panel Surface	Anti-glare
	Analog	RGB analog (75 ohms, 0.7/1.0 Vp-p)
	Digital	DVI-D (TMDS, 100 ohms)
	Frequency	F _H : 24~82kHz, F _V : 50~75Hz
COMPATIBILITY	Sync	H/V separated (TTL), composite sync-on-green
	PC	VGA up to 1440x900 non-interlaced
CONNECTOR	Mac®*	Power Mac™ G3/G4/G5 up to 1440x900
	Analog	15-pin mini D-sub (VGA)
AUDIO	Digital	DVI-D
	Power	3-pin AC plug (CEE22)
POWER	Speakers	2x2-watt
	Voltage	AC 100~240V (universal), 50/60Hz (auto switch)
CONTROLS	Consumption	15W (typ)
	Basic	Power, 1, down, up, 2
ERGONOMICS	OSD	Auto image adjust, brightness, contrast, input select (analog, digital), ViewMatch® color adjust (sRGB, 9300K, 7500K, 6500K, 5400K, default, user color - RGB), information (resolution, H/V frequency, pixel clock, model number, serial number), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall
	Tilt	Down 5°, Up 20°
OPERATING CONDITIONS	Temperature	31~104° F (0~40° C)
	Humidity	10~90% (non-condensing)
DIMENSIONS (W x H x D)	Physical with stand	17.7" x 17.0" x 8.2" (450mm x 434mm x 209mm)
	Physical without stand	17.7" x 13.4" x 2.6" (450mm x 341mm x 66mm)
	Packaging	21.5" x 20.3" x 6.4" (546.1mm x 515.6mm x 162.6mm)
WEIGHT	Net with stand	10.3 lb. (4.7 kg)
	Net without stand	8.1 lb. (4.0 kg)
	Gross	13.6 lb. (6.2 kg)
VESA® MOUNT		100mm x 100mm
REGULATIONS		UL, cUL, FCC-B, CB, CE, ENERGY STAR®, NOM, GS (covers GS), ERGO (ISO13406-2 & MPR II), MPR II, GOST-R + 20 original copies hygienic, SASO, PCBC, VCCI, BSMI, CCC, PSB, C-TICK, MIC (KCC), WEEE, RoHS
POWER MANAGEMENT		Meets MPR II and ENERGY STAR® standards
PACKAGE CONTENTS		LCD display, power cable, VGA video cable, DVI cable, audio cable, Quick Start Guide, ViewSonic Wizard CD (User Guide and drivers)
WARRANTY		Three-year limited warranty on parts, labor and backlight.

Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2009 ViewSonic Corporation. All rights reserved. [14552-00B-09/09] VX1932wm-LED

ViewSonic®
See the difference®

For more product information, visit us on the web at ViewSonic.com