

WPL25

BARCODE PRINTER



The WPL25 compact desktop printer is designed to quickly and efficiently print direct thermal barcode labels up to 2 inches wide. The high-quality, double-walled clamshell design makes the WPL25 ideal for specimen labeling and patient tracking in healthcare, product and shelf labeling in retail and point-of-sale applications, and small or home office mailing, shipping, and file folder labeling.

Small and compact, the WPL25 prints labels at speeds up to 5 inches per second at 203 dpi print resolution and is supported by 8 MB SDRAM and 4 MB Flash memory. Wasp's direct thermal printer enables you to maximize workplace efficiency and productivity by using a 200 MHz processor and expandable memory option of up to 4 GB Flash. With the ability to hold up to 5-inch outside diameter media rolls, the WPL25 makes it quick and easy to change media by simply lifting the cover and placing your labels into the spring loaded media guide.

Wall mountable holes on the bottom cover make the WPL25 suitable for wall mounting or desktop printing – giving you the option to free up desk space. Fitted with serial and USB interfaces and supported by WPL, ZPL emulation, and EPL emulation, the WPL25 provides versatile connectivity for integration into today's busy environment.

■ WASP WPL25 FEATURES

- Direct thermal print technology
- ▶ Print labels up to 2.13 inches wide
- ▶ Print speed up to 5 inches per second
- ▶ 203 dpi print resolution
- ▶ 8 MB SDRAM, 4 MB Flash
- MicroSD slot allows for Flash memory expansion up to 4 GB
- ▶ 200 MHz, 32-bit RISC processor
- ▶ WPL, ZPL emulation, and EPL emulation
- ► Supports 5-inch outside diameter media roll
- ► USB 2.0 and Serial connectivity

BENEFITS

- Print high performance labels for healthcare, retail, shipping, and office environments
- Double-walled clamshell design makes it easy to load media
- ▶ WPL, ZPL emulation, and EPL emulation provides for versatility and compatibility with any application
- 200 MHz processor and 8 MB SDRAM, 4 MB Flash allows for quick label processing



WPL25

BARCODE PRINTER



■ SPECIFICATIONS

	INO	
STANDARD FEATURES	Printing method Resolution	Direct thermal
	Print speed	203 dpi (8 dots / mm) Up to 5 in. per second
		2.13 in. (54 mm)
	Maximum print width	
	Maximum print length	90 in. (2,286 mm)
	Standard memory	8 MB SDRAM, 4 MB Flash
	Memory expansion	MicroSD memory expansion slot for use with Flash memory up to 4 GB
	Sensors	Label gap, black line, head open
	Cabinet	Double-walled ABS plastic
	Operation panel	One power switch, one feed button, one LED (three color)
	Dimensions	8.23 in. L x 4.29 in. W x 6.73 in. H (209 mm L x 109 mm W x 171 mm H)
	Net weight	2.6 lbs (1.8 kg)
	Command set	WPL, ZPL emulation, EPL emulation
OPERATIONAL CHARACTERISTICS	Communication interfaces	USB 2.0, RS232
	Operating temperature	41°F to 104°F (5°C to 40°C)
	Storage temperature	-40°F to 140°F (-40°C to 60°C)
	Certifications	FCC Class B, CE Class B, C-Tick Class B, UL, CUL, TUV/Safety, CCC
MEDIA	Media width	0.59 in. to 2.36 in. (15 mm to 60 mm)
	Media diameter (max.)	5 in. OD (127 mm) with 1 in. or 1.5 in. core
	Ribbon length (max.)	n/a
FONTS, GRAPHICS SYMBOLOGIES	Barcode symbologies	1D Barcodes: Code 39, Code 93, Code 128 UCC, Code 128 subsets A.BC, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2 (5) digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 DataBar, Code11 2D Barcodes: PDF-417, Maxicode, DataMatrix, QR code, Aztec
	Resident fonts	8 alpha-numeric bitmap fonts, 1 Monotype Image® CG Triumvirate Bold Condensed scalable font
	Font rotation	0, 90, 180, 270 degrees
PART NUMBERS	633808403836	WPL25 Desktop Barcode Printer
	633808403898	WaspProtect for WPL25 Desktop Barcode Printer