

Basic Specifications:

- » 4 Seconds/Card Print Speed
- » Convenient Front Card Loading and Output
- » Monochrome Single- Sided Card Printing
- > USB/Parallel or USB/Serial Interfaces
- » 50 Card Capacity Feeder



P205

Card Printing Is Easier Than Ever

The Zebra P205 is an intelligent, economical, single-sided monochrome card printer with convenient, easy-to-use features to produce personalized cards on-demand with text, or bar codes for lower volume applications.

Use the P205 card printer to print:

- » Employee ID cards
- » Loyalty cards
- » Personalised Gift and Membership cards

Zebra P205 Advantages

Operator Convenience: Patented openACCESS[®] clam-shell design, easy-to-use "load and go" ribbon cartridge system, quick reference Pocket Guide, Windows® 98, ME, NT, 2000 and XP printer drivers with install wizard

Economical Operation: Low cost printer for low-volume applications



Card Printer Solutions

P205

Card Printer Product Specifications

General Specifications

- » High speed card printing
- » 900 cards/hour for resin black (K)
- » 2MB image memory standard/1MB flash memory
- » Windows[®] drivers for 98, ME, NT, 2000 and XP
- » Patented openACCESS[®] clamshell design
- » Front card loading and output
- » Multi-Function Button with LED indicator ring
- » One year warranty
- » One year (unlimited passes) printhead warranty

Printing

- » Monochrome thermal transfer printing
- » 4 seconds/card monchrome
- » 300 dpi (11.8 dots/mm) print resolution

Bar Codes

- » Code 39, Code 128 B & C with & without check digit
- » 2 of 5 & 2 of 5 Interleaved
- » UPC-A. EAN 8 & EAN 13
- » PDF-417 2D bar code and other symbologies can be printed via Windows drivers

Fonts

» True Type fonts via Windows driver

Card Specifications

- » Types: PVC, PVC Composite
- » Card width/length: ISO CR-80-ISO 7810, 2.12" (54mm) x 3.38" (86mm)
- » Magnetic Stripe-ISO 7811
- » Card thickness: 30 mil (.76mm)
- » Card feeder capacity: 50 cards (30 mil)

Technologies Corporation

» Card output hopper capacity: 20 cards (30 mil)

Ribbon Specifications

» Monochrome: 500 cards/roll

Communications Interface

- » USB and Centronics Parallel
- » USB and RS232 Serial

Mechanical (includes card feeder)

- » Width: 7.16in (182mm)
- » Depth: 11.9in (303mm)
- » Height: 7.1in (180mm)
- » Weight: 6.4lbs (2.9kg)

Electrical

- » 110 ~ 240 Volts AC, 50 ~ 60 Hz (auto switching)
- » FCC Class B, CE, UL and CUL approved

Environmental

- » Operating Temperature: 60°F to 86°F (15°C to 30°C)
- » Operating Humidity: 20% to 65% non-condensing
- » Storage Temperature: 23°F to 158°F (-5°C to 70°C)
- » Storage Humidity: 20% to 70% non-condensing
- » Ventilation: Free air

Options

- » Magnetic encoder, tracks 1 & 2
- » Cleaning supplies
- » Service manual

http://cards.zebra.com

EISO 9001

An ISO 9001 registered company ©2003 ZIH Corp. Specifications listed are for base model printers with standard features only unless otherwise notes. Specifications subject to change without notice. All product and brand names are trademarks of their respective companies. All rights reserved. All Copyrights, Trade and Service Marks shown or depicted herein are registered by their owners. No infringement is made for or implied by the use thereof. **Part No. P205-10/03**

North America

Zebra Technologies Corporation **Card Imaging Division** 1001 Flynn Road Camarillo, CA 93012-8706 USA

Telephone: +1 805 579 1800 Fax: +1 805 579 1808 Toll free in US: 800 452 4056 e-mail: cards@zebra.com

Europe, Middle East, Africa

Zebra Technologies Corporation **Card Imaging Division** The Valley Centre, Gordon Road High Wycombe Buckinghamshire HP13 6EQ, UK Telephone: +44 870 241 1527 Fax: +44 870 241 0765 e-mail: eurosales@zebra.com

Asia Pacific

Zebra Technologies Corporation **Card Imaging Division** 1 Sims Lane #06-11 387355 Singapore Telephone: +65 6858 0722 Fax: +65 6885 0836 e-mail: asiasales@zebra.com

*Optimised for use with Zebra media

R

Latin America

Zebra Technologies Corporation **Card Imaging Division** 6175 NW 153rd St #121 Miami Lakes, FL 33014 USA Telephone: +1 305 558 3100 Fax: +1 305 558 8485 e-mail: latinsales@zebra.com