



SHIPPING & RECEIVING LABELING QUALITY TESTING FULFILLMENT

Light Weight & Durable

All metal construction, yet under 100 pounds.

Low Maintenance

Reliable all-day power for your workflow

Intelligent Fleet Management

Maestro system provides cart & fleet analytics for optimization and process improvement

Power Specifications

Target Run Time

Charge Time (from empty)

Battery Life

Technology Supported

Up to 12 Hours

4 Hours

Up to 10 years* (Per User Manual)

Desktop Thin-Client, SMF PC, or All-in-one PC Industrial Desktop Thermal Printer (Up to 2) Wired or Wireless Barcode Scanners Wired or Wireless RFID Scanners

PAC Max Mobile Workstation





Accessories



Dual Monitor Holder (H)



Waste Basket Holder



Dual Monitor Holder (V)



Monitor Scanner Holder

General Specifications

Height (Work Surface) 44" (1117 mm) Width 38.6" (981 mm) Depth 25.2" (641 mm) Weight (Cart & Power) 122 Lbs. (55.3 kg) Work Surface Size (W x D) 38" x 20.5" (965 mm x 520 mm) Base Size (W x D) 38.1" x 23.6" (970 mm x 600 mm) Casters 5 Inch 100 - 240 VAC Input Voltage

700 W/t (O-time - ----il-b)

Continuous Output Power 700 W* (Options available contact us)
Surge Power 1000 W

Operating Temperature 32 F to 104°F (0° C to 40C)