



# Brother *Titan Industrial Printer* Series

4-INCH BARCODE & LABEL PRINTERS

High speed & increased durability.

**Product datasheet** 

TJ-4420TN

TJ-4520TN





# Print ultra-fast. Again. And again. And again.

Introducing the TJ-4420TN and TJ-4520TN of the Brother 4-inch *Titan Industrial Printer* series. These printers produce high-quality labels at staggering 12ips and 14ips print speeds and up to 300dpi. Keep going strong with durable construction that helps you cross labeling finish lines.

The Brother *Titan Industrial Printer* series produces consistently crisp barcode labels at top speeds. Push the boundaries of what you can accomplish with refreshingly easy integration designed to drop in and a complete set of connectivity choices. Experience it all with some of the most affordable price points and subscription<sup>1</sup> options available. Then, discover unmatched support that's "at your side" for life.<sup>2</sup>

	Dual WIFI Bluetooth Module	<b>USB</b>	Ethernet	Serial	•••• DPI	<b>≡</b> ( <b>1</b> ) Speed	Direct Thermal	Thermal Transfer	Cutter/Peeler
TJ-4420TN	Optional	•	•	•	203	14 ips max	•	•	Optional
TJ-4520TN	Optional	•			300	12 ips max			Optional

# **Key features**

- **Performance:** Produce quality, scannable barcodes at up to 14ips<sup>3</sup>. You can also scale up to 300dpi for visibly sharp resolutions.
- **Support:** Backed by an industry-leading Two-year Premier Limited Warranty<sup>4</sup>, printhead replacement perks program<sup>5</sup>, and responsive, lifetime<sup>2</sup> customer support.
- Integration: Seamlessly integrate with YOUR system using a full suite of included emulations, SDKs, and drivers.
- **Versatile connectivity:** All models come standard with Ethernet/LAN, USB 2.0, host USB, and RS232C Serial, plus a dual Wi-Fi<sup>®</sup> and *Bluetooth*<sup>®</sup> connectivity option
- Buy or subscribe: Upfront affordability with some of the lowest price points in the industry or subscription<sup>1</sup> options for one low monthly fee.
- Usability: See printer status easily with a bright multicolor status light and LCD display.

<sup>&</sup>lt;sup>1</sup> Shift & Print Subscription Service is subject to credit approval.

<sup>&</sup>lt;sup>2</sup> For the life of the product.

Sased on performance tests using Brother certified media, actual results may vary in actual applications.

Warranty includes the printhead, which is covered up to 2 years or 1 million linear inches, whichever comes first. For full details, contact your Brother Sales Representative or visit our Warranty Page

Get replacement printheads at up to 56% off the list price while the machine is under warranty and serviced by Brother.



# Industry applications

These industrial printers are ideally suited for longterm use in warehouses, manufacturing and across the supply chain.



#### **Transport & Logistics (Warehouse)**

- Shipping labels
- Product ID labels
- Secondary packing labels
- Order preparation "picking"
- Pallet labels

#### Manufacturing

- Packing labels
- Shipping labels
- Parts / product labels
- Secondary packing labels
- Storage labels

#### Retail

- Shipping labels
- Returns labels
- Product labels



#### **Supplies**

Find Premium label rolls and ribbon types for all your applications. Custom options also available.



#### **Accessories**

We offer optional peeler, cutter, and dual Wi-Fi & Bluetooth interface, as well as replacement platen roller and printheads.



### **Extended** warranty service

Extend the useful life of your printer by adding an extended service program at any point while your printer is still under warranty.

## Get in contact

800-543-6144 mobilesales@brother.com www.brothermobilesolutions.com Software tools for easy integration and label design











	TJ-4420TN	TJ-4520TN		TJ-4420TN	TJ-4520TN		
General			Printing				
Box Contents	Printer, Power Cord, USB Documentation	Cable,	Print technology	Direct Thermal and Thermal Transfer			
Dimensions (W x H x L)	10.9" x 12.8" x 19.8" (276mm x 326mm x 502	2mm)	Print Head Resolution	203dpi (8 dots/mm)	300dpi (12 dots/mm)		
Weight	33.8 lbs. (15.4kg)		Print Engine speed	Up to 14 ips (356mm/sec) <sup>1</sup>	Up to 12 ips (305mm/sec) <sup>1</sup>		
Power Specifications	Built-In Power Supply (Input: 100 - 240VAC 50)	/60Hz 4.0A – 2.0A)	Media/Print Width	4.5" (114mm) / 4.1" (104mm)			
Printer Memory	256MB SDRAM, 512MB Optional 32GB MicroSD			Linear: Code 11 (USD-8), Code 39, Code 93, Code 128 with subsets A/B/C, UPC-A, UPC-E, EAN-8, EAN-13, UPC and EAN 2- or 5-digit extensions, GS1-128			
Control panel	6 Keys, 3 Color Status LE TFT LCD Control Panel, D Interface Ports		Resident Barcodes	(UCC/EAN-128), MSI Plessey, POSTNET, Standard 2-of-5 (IATA), Industrial 2-of-5, Interleaved 2-of-5, ITF-14, EAN-14, LOGMARS, Codabar (NW-7), Planet, Telepen, Deutsche Post Identcode, Deutsche Post Leitcode, Datalogic 2-of-5 (China Post) 2D: CODABLOCK F, PDF417, Code 49, GS1 DataMatrix, MaxiCode, QR Code, TLC39,			
Real Time Clock	Standard						
Audio Device	Standard						
Operating Systems	Windows Server 2019/2l Windows 10/8.1/7 (64-b Mac OS X® 10.11.x, macOS® 10.12.x or High	it and 32-bit),	Printer Sensors	MicroPDF417, GS1 DataBar (RSS), Aztec Code  Full Width Moveable Gap (Transmissive) and Black Mark (Reflective), Ribbon Encoder and Ribbon End, Head Open, Peeler (Optional)			
SDK Support	Windows Server 2019/20 2012/2008 R2/2008, Will Windows Victor Andreid T	ndows 10/8.1/8/7,	Media Type	Label and Tag: Roll or Fanfold / Die Cut or Continuous			
	Windows Vista, Android <sup>™</sup> iOS v9.0 or Higher		Media Roll Size	8.00" (203.2mm) Outer Diameter, Wound Out 1.5" (38.1mm) or 3" (76.2mm) Core Inside Diameter			
In Box Software	Seagull BarTender UltraL Software Application, Bro Management Software T	other Printer	Media Loading	Internal: 1.5" Spindle, Compatible up to 3" Core External: Rear or Bottom Feed (External Roll and Fanfold)			
Printer Languages	FBPL II, ZPL II®, EPL2, DF	PL		Width: 0.79" - 4.5" (20mm - 114mm), Thickness: 2.36mil – 11mil (0.06mm - 0.28mm), Minimum Length (Tear): 0.2" (5mm), Minimum Length (Cutter): 1.0" (25.4mm), Minimum Length (Peeler): 0.5" (12.7mm)			
ENERGY STAR Certified	Energy Star 3.0		Media Specifications				
Operating Temperature/Humidity	32°F - 104°F (0°C - 40°	C) / 25% - 85%					
Storage Temperature/Humidity	-40°F - 140°F (-40°C - 6	60°C) / 10% - 90%	Ribbon Types	Wax, Resin, Semi (Wax / Resin)			
Connectivity			Ribbon Length	1,968' (600m) / 3.5" (90mm) Outer Diameter, Wound In/Out or 1,476' (450m) / 3.2" (81.3mm) Outer Diameter, Wound In/Out or 984' (300m) / 2.64" (67mm) Outer Diameter, Wound In/Out on 1" (25.4mm) Core Inside Diameter (No Notch)			
Standard Interfaces	Ethernet LAN (10/100Base Dual Host USB, RS232C						
Optional Interfaces	nal Interfaces  Dual Wi-Fi WLAN (5GHz 802.11a/n, 2.4GHz 802.11b/g/n) & Bluetooth 5.0		Ribbon Width	1.0" - 4.5" (25.4mm - 11			
	WLAN: IPv4, ARP, ICMP, U Client, DHCP FQDN Option		Ribbon Take Up Core	Ribbon Quick Release Ta No Ribbon Take Up Core			
Security Protocols	LAN: ARP, MAC, BOOTP, D FTP Server, HTTP Server, SMTP Client, SNMP V1, To RAW 9100, IPv4, ICMP, IG	HCP, DNS, WINS, SNTP Client, elnet, LPR/LPD,	Optional Accessories	Wi-Fi & Bluetooth Interface (PA-WB-001), Automatic Cutter (PA-CU-005), Label Peeler with Liner Rewinder (PA-LP-006), Print Head 203dpi (LBX097001), Print Head 300dpi (LBX098001), Platen Roller (LBX101001)			
Wireless Security	802.11i, WEP 64/128bit, (TKIP/AES), WPA2-Enterp (EAP-FAST, PEAPv0, EAP-	rise					
Bluetooth Profiles	SPP, GATT (BLE)						

<sup>&</sup>lt;sup>1</sup>Based on performance tests using Brother certified media, actual results may vary in actual applications

Images are for illustrative purposes only. Actual output (such as font and margins) may vary. All specifications subject to change without notice.

Brother is a trademark or registered trademark of Brother Industries, Ltd, in the United States. All other trademarks and registered trademarks are the properties of their respective companies.